

FATIGUE PROPERTY MAPPING



KNOW YOUR MATERIAL

MATERIAL CHARACTERIZATION



Endurica's Fatigue Property Mapping™ service provides a comprehensive inventory of the fatigue capabilities of your material.

Get Durability Right® in your development and analysis projects with our uniquely efficient, reliable, and physics-based testing protocols.

BENEFITS

- Material parameters ready to use with durability simulation codes, including Endurica CL™, Endurica DT™, Endurica EIE™, and fe-safe/Rubber™
- Full support for both nucleation (ϵ -N) or (σ -N) and crack propagation (da/dN) analysis methods.
- Accurate and timely results via uniquely reliable and productive test strategies.
- Reduced risk and cost of development iterations when you take your material's fatigue capabilities into account.
- Leverage your material's full potential by properly aligning its capabilities with the application's demands.

| | | |
|--|------------------|---|
| <h3>Hyperelastic Module</h3> <p>Simple, planar, and equibiaxial tension, Mullins effect</p> | | FPM H |
| <h3>Core Fatigue Module</h3> <p>Fully relaxing behavior from both nucleation and fracture mechanical perspectives</p> | | FPM C |
| <h3>Intrinsic Strength Module</h3> <p>Quantify endurance limits</p> | FPM IS | <h3>Thermal Modules</h3> <p>Quantify dissipative properties, thermal properties</p> |
| <h3>Non Relaxing Module</h3> <p>Quantify strain crystallization, minimum and mean strain effects</p> | FPM NR | <div style="display: flex; justify-content: space-around;"> <div>FPM TB BASIC</div> <div>FPM TA ADVANCED</div> <div>FPM TM K/ WILLIAMS-LANDEL-FERRY</div> </div> |
| <div style="display: flex; justify-content: space-between;"> <div>FPM AB</div> <div> <h3>Ageing Module</h3> <p>Quantify endurance limit, estimate ageing rate of stiffness, intrinsic and ultimate strength</p> </div> <div>FPM AM MASTER CURVE</div> </div> | | <h3>Cyclic Softening Module</h3> <p>Quantify cyclic softening effects</p> |
| <div style="display: flex; justify-content: space-between;"> <div>FPM O2A ADV</div> <div> <h3>Oxygen Diffusion Module</h3> <p>Aerobic Effects on Ageing</p> </div> <div>FPM O2B BASIC</div> </div> | | <h3>Reliability Module</h3> <p>Weibull statistics for strength and crack precursor size populations</p> |
| <h3>Ozone Module</h3> <p>Quantify ozone attack critical energy and rate</p> | FPM O3 | <h3>Creep Module</h3> <p>Creep crack growth rate effects</p> |
| | | <h3>Chip & Cut Module</h3> <p>Chip, chunk and cut testing for wear</p> |




GET DURABILITY RIGHT[®] WITH ENDURICA'S FATIGUE PROPERTY MAPPING

Hyperelastic Module

Provides basic information needed for Finite Element Analysis and initial transient softening (Mullins effect)


- Simple tension
- Planar tension
- Biaxial tension



Core Fatigue Module

Pre-requisite for any fatigue analyses


- Provides basic fatigue crack growth rate curve
- Strain-life curve
- Crack precursor size



Intrinsic Strength Module

Required for safety factor / infinite life / fatigue limit analysis


- Recommended for cases with fatigue life longer than 10^6 cycles



Ageing Module

Recommended for cases with fatigue life longer than 10^6 cycles, and when ageing must be taken into account

- Quantify evolution of stiffness and crack growth parameters
- Quantify Arrhenius Ageing Law parameters



Thermal Modules

Quantify dissipative / thermal properties, temperature dependence


- Basic module for cases involving significant self-heating or thermal gradients
- Advanced module for improved accuracy in structural and heat transfer analyses
- Thermal Effects module (K/WLF) used to determine strain, temperature and frequency dependence of viscoelastic storage and loss modulus



Non Relaxing Module

Recommended for cases where cyclic minimum loading is greater than zero and material may strain crystallize

- Test is run under range of nonrelaxing ($R > 0$) conditions



Ozone Module

Quantify ozone attack critical tearing energy and rate


- Required when rubber is susceptible to ozone attack and operating in environment with ozone



Oxygen Diffusion Module

Recommended when the potential for aerobic effects on ageing should be checked


- Use with
- Fick's law mass diffusion
 - Gillen et al's basic autooxidation scheme



Reliability Module

Recommended when probability of failure needs to be estimated


- Weibull analysis parameters relating frequency of occurrence to size of crack precursor



Creep Module

Recommended for cases involving long periods under static load


- Time-dependent crack growth is characterized here (rather than cycle-dependent crack growth)



Cyclic Softening Module

Recommended for cases where stiffness loss limits durability


- Use with Endurica DT cosimulation feature
- Displacement control experiment records the evolution of the peak stress with cycles



Chip & Cut Module

Recommended for cases where harsh or abrasive environments may cause cutting and chipping on an elastomeric contact surface

- Use with
- Tire tread applications
 - Belts - especially in mining
 - Impact damage applications



Endurica
Get Durability Right[®]

Endurica LLC
219 West Main Cross St., Suite 201
Findlay, Ohio 45840 USA
+1 419.957.0543

Endurica Europe S.à r.l.
9, avenue des Hauts-Fourneaux
L-4362, Esch-sur-Alzette Luxembourg
+352 691 398 233